

## UPC LISTED PIPE WRAP TAPE - 10 MIL.



Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	Select Model Below
<b>UPC LISTED PIPE WRAP TAPE</b>					
H30020	HPPWT10100	1" x 100' BLACK PIPE WRAP TAPE (10 MIL.)	1	48	<input type="checkbox"/>
H30021	HPPWT102100	2" x 100' BLACK PIPE WRAP TAPE (10 MIL.)	1	24	<input type="checkbox"/>
H30022	HPPWT104100	4" x 100' BLACK PIPE WRAP TAPE (10 MIL.)	1	12	<input type="checkbox"/>

### 10 MIL. TAPES



### TECHNICAL INFORMATION

<b>THICKNESS</b>	10 mils (0.25 mm)
<b>TENSILE STRENGTH</b>	9 kg (25mm)
<b>ELONGATION AT BREAK</b>	200%
<b>ADHESION TO STEEL</b>	.56kg (25mm)
<b>ADHESION TO BACKING</b>	.56 kg (25mm)
<b>DIELECTRIC STRENGTH</b>	7000 volts
<b>UNWIND FORCE</b>	800g (25mm)

#### Uses:

- Corrosion protection for metal piping systems above and below ground.
- Corrosion protection for fittings and joints on mill coated pipe.
- Corrosion protection of electrical conduit & fittings.

#### Features:

- Resists corrosive action by salt water, soil acids, alkalis and salts.
- Prevents dielectric corrosion between buried steel pipe and soil minerals.
- Resists the effects of outdoor weathering and sunlight exposure.
- High abrasion resistance.
- Highly conformable over a wide temperature range.
- Excellent insulating properties.
- Resists commonly encountered chemicals and chemical vapors.
- Protects against fungus and bacteria.
- Standard widths.



JOB NAME:

JOB LOCATION:

CONTRACTOR:

DATE:

ITEM TAG:

ENGINEER APPROVAL:

DATE:

PART NUMBER:

## UPC LISTED PIPE WRAP TAPE - 20 MIL.



Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	Select Model Below
<b>UPC LISTED PIPE WRAP TAPE</b>					
H30023	HPPWT201100	1" x 100' BLACK PIPE WRAP TAPE (20 MIL.)	1	48	<input type="checkbox"/>
H30024	HPPWT202100	2" x 100' BLACK PIPE WRAP TAPE (20 MIL.)	1	24	<input type="checkbox"/>

### 20 MIL. TAPES



### TECHNICAL INFORMATION

<b>THICKNESS</b>	20 mils (0.50 mm)
<b>TENSILE STRENGTH</b>	16 kg (25mm)
<b>ELONGATION AT BREAK</b>	200%
<b>ADHESION TO STEEL</b>	.56kg (25mm)
<b>ADHESION TO BACKING</b>	.56 kg (25mm)
<b>DIELECTRIC STRENGTH</b>	11000 volts
<b>UNWIND FORCE</b>	800g (25mm)

#### Uses:

- Corrosion protection for metal piping systems above and below ground.
- Corrosion protection for fittings and joints on mill coated pipe.
- Corrosion protection of electrical conduit & fittings.

#### Features:

- Resists corrosive action by salt water, soil acids, alkalies and salts.
- Prevents dielectric corrosion between buried steel pipe and soil minerals.
- Resists the effects of outdoor weathering and sunlight exposure.
- High abrasion resistance.
- Highly conformable over a wide temperature range.
- Excellent insulating properties.
- Resists commonly encountered chemicals and chemical vapors.
- Protects against fungus and bacteria.
- Standard widths.



JOB NAME: \_\_\_\_\_

JOB LOCATION: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

DATE: \_\_\_\_\_

ITEM TAG: \_\_\_\_\_

ENGINEER APPROVAL: \_\_\_\_\_

DATE: \_\_\_\_\_

PART NUMBER: \_\_\_\_\_