

SPECIFICATION SUBMITTAL SHEET

F2159 PLASTIC PEX FITTINGS

- These fittings are intended for use in cold and hot water distribution (potable) systems.
- Barbed end connections are designed for insertion into PEX tubing that conforms to ASTM F876 and F877.
- Designed for use with copper crimp rings (offered seperately) that are manufactured in compliance with ASTM F 1807 and stainless steel clamp rings that are manufactured in compliance with ASTM F 2098.
- Available in 1/2", 3/4" and 1" PEX Tubing sizes in EIGHT (8) configurations.
- Working Pressure, Non-Shock (PSI) 180° F @ 100 psi, max.
- Chemical and Corrosion Resistant.



CERTIFICATIONS / LISTING - Third Party Certified

ANSI/NSF 14: Plastic piping system components and related materials ANSI/NSF 61: Drinking water system components health effects CSA B137.5: Thermoplastic pressure piping compendium

STANDARDS:

ANSI/ASME B1.20.1: Pipe threads, general purpose, Inch ASTM F2159: Plastic insert fitting with crimp ring connection ASTM F2098: Metal or plastic insert fitting with a stainless steel clamp ASTM D6394: Standard specification for Sulfone Plastic Resin

-MATERIAL SPECIFICATION -

	PART	MATERIAL	SPECIFICATION
1	All plastic PEX fitting configurations	Modified Polyphenylsulfone	ASTM D 6394



JOB NAME:			
JOB LOCATION:			
CONTRACTOR:	DATE:	ITEM TAG:	
ENGINEER APPROVAL:	DATE:	PART NUMBER:	