

AVAILABLE COLORS

- WHITE** - 53501
- BLACK** - 53502
- GREY** - 53503
- LIMESTONE** - 53507

High Quality
Aluminum Tube



535 POLYURETHANE

PROFESSIONAL GRADE • CONSTRUCTION • MULTI-PURPOSE

- Very good adhesion to most substrates
- Qualifies for LEED credits
- Good UV Resistance and color stability
- Good weather resistance
- Long life reliability
- Interior & exterior uses
- Paintable with most paint systems
- Non-yellowing and non-staining

THE IDEAL SEALANT/ADHESIVE FOR:

- Securing Roof & Sidewall Penetrations
- Joints between window frames, door frames, and walls
- Shrinking joints in concrete floors
- Joints with large movement

LIMITATIONS

- Does not adhere to glass, PE, PP, or PTFE. It is the sole responsibility of the user to test the adhesion to the substrate for suitability.
- Do not apply in the presence of uncured silicone sealants, alcohol, or other solvent cleaners.
- Contact with bitumen, tar, or other plasticizer releasing materials such as EPDM, neoprene, butyl, etc., is to be avoided since it can give rise to discoloration and loss of adhesion.

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. **IN CASE OF EYE CONTACT**, flush eyes with water for 15 minutes. Obtain medical attention. **IN CASE OF SKIN CONTACT**, remove from skin and flush with water. **KEEP OUT OF THE REACH OF CHILDREN.** For safe handling information on this product, consult the Safety Data Sheet (SDS).

TYPICAL PROPERTIES

Uncured

Flow sag or slump *NIL*
Skin time..... *50-60 minutes*

Cured

Durometer Shore A Hardness *30±5 points*
Specific Gravity *1.53*
Tensile Strength *165 PSI*
Elongation *>800%*
Modulus..... *85 PSI*
Shrinkage *NIL*
Service Temperature..... *-22°F to 194°F*
Application Temperature *41°F to 86°F*

Primers may be required for certain substrates.
Information on this data sheet is subject to change without notice and should not be used for writing specifications.
For additional information on specific applications, contact Soudal.

JOB NAME:

JOB LOCATION:

CONTRACTOR:

DATE:

ENGINEER APPROVAL:

DATE:

ITEM TAG:

PART NUMBER:

Model #	DESCRIPTION	Master Carton Quantity	List Price (\$)	MAKE SELECTION BELOW
BOSS53501	Polyurethane Adhesive Sealant WHITE	12	\$ 9.72	<input type="checkbox"/>
BOSS53502	Polyurethane Adhesive Sealant BLACK	12	\$ 9.72	<input type="checkbox"/>
BOSS53503	Polyurethane Adhesive Sealant GREY	12	\$ 9.72	<input type="checkbox"/>
BOSS53507	Polyurethane Adhesive Sealant LIMESTONE	12	\$ 9.72	<input type="checkbox"/>

www.hydrapro.biz | (800) 849-4844 | Fax (877) 249-8435

Atlanta (GA) • Dallas (TX) • Houston (TX) • Pompano Beach (FL) • Jackson (MI)