


## F1960 PPSU PLASTIC PEX FITTINGS

- These fittings are intended for use in cold and hot water distribution (potable) systems.
- Barbed end connections are designed for insertion into PEX (ASTM F876 & F877) and PE-RT (ASTM F2769).
- Designed for use with cold expansion rings that are manufactured in compliance with ASTM F1960
- Available in 1/2" - 2" PEX Tubing sizes in FOUR (4) configurations.
- **Working Pressure, Non-Shock (PSI)** 180° F @ 100 psi, max.
- Chemical and Corrosion Resistant.



### CERTIFICATIONS / LISTING - Third Party Certified

ANSI/NSF 14: Plastic piping system components and related materials  
 ANSI/NSF 61: Drinking water system components health effects  
 CSA B137.5: Thermoplastic pressure piping compendium

### STANDARDS:

ANSI/ASME B1.20.1: Pipe threads, general purpose, Inch  
 ASTM F1960: Requirements for cold expansion using PEX reinforcing rings  
 ASTM D6394: Standard specification for Sulfone Plastic Resin

## MATERIAL SPECIFICATION

PART	MATERIAL	SPECIFICATION
1 All plastic PEX fitting configurations	Modified Polyphenylsulfone	ASTM D 6394



JOB NAME: \_\_\_\_\_

JOB LOCATION: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

ENGINEER APPROVAL: \_\_\_\_\_

DATE: \_\_\_\_\_

DATE: \_\_\_\_\_

ITEM TAG: \_\_\_\_\_

PART NUMBER: \_\_\_\_\_