

SPECIFICATION SUBMITTAL SHEET

DROP-IN ANCHORS



PART #	MODEL #	DESCRIPTION (SIZE)	STANDARD ORDER QUANTITY	MASTER Carton QTY.	SELECT Model Below		
DROP-IN ANCHORS —							
H98350	HPFDA14J	DROP IN ANCHOR, 1/4", 100/JAR	1/JAR	10			
H98351	HPFDA38J	DROP IN ANCHOR, 3/8", 100/JAR	1/JAR	8			
Н98352	HPFDA12J	DROP IN ANCHOR, 1/2", 50/JAR	1/JAR	8			
H98353	HPFDA58J	DROP IN ANCHOR, 5/8", 50/JAR	1/JAR	6			

PRODUCT FEATURES —

- Heavy-Duty Anchor is Set by an External Expanding Plug and Setting Tool
- Ideal for Hanging Pipe, Duct Work, Machinery, etc.
- Once Hole is Drilled, Anchor is Placed in Hole and Set by Hammer Blow Directly on Setting Tool
- Can be Used in Cinder Block or Concrete Carbon Steel; Zinc-Plated
- UL Listed Sizes Include 3/8" Packaged in Reusable Plastic Jar
- Setting Tool Included for Every 100 Anchors Purchased

PART#	MODEL#	ANCHOR DIAMETER	DRILL BIT DIAMETER	MIN. EMBEDMENT	REQUIRED TORQUE	2000 PSI CONCRETE TENSION (LBS)	4000 PSI CONCRETE TENSION (LBS)
H98350	HPFDA14J	1/4"	3/8"	1"	5	939	2,067
H98351	HPFDA38J	3/8"	1/2"	1-9/16"	10	1,560	3,995
H98352	HPFDA12J	1/2"	5/8"	2"	20	3,105	4,110
H98353	HPFDA58J	5/8"	7/8"	2-1/2"	40	3,323	5,750

JOB NAME:		JOB LOCATION:	
CONTRACTOR: DATE:		ITEM TAG:	
ENGINEER APPROVAL:	DATE:	PART NUMBER:	