

HAMMER DRIVE ANCHORS



PART #	MODEL #	DESCRIPTION (SIZE)	STANDARD ORDER QUANTITY	MASTER CARTON QTY.	SELECT MODEL BELOW
HAMMER DRIVE ANCHORS					
H98364	HPFHD14X34J	HAMMER DRIVE ANCHOR, 1/4" X 3/4", 100/JAR	1 / JAR	10	☐
H98365	HPFHD14X1J	HAMMER DRIVE ANCHOR, 1/4" X 1", 100/JAR	1 / JAR	10	☐
H98366	HPFHD14X114J	HAMMER DRIVE ANCHOR, 1/4" X 1-1/4", 100/JAR	1 / JAR	8	☐
H98367	HPFHD14X112J	HAMMER DRIVE ANCHOR, 1/4" X 1-1/2", 100/JAR	1 / JAR	10	☐
H98368	HPFHD14X2J	HAMMER DRIVE ANCHOR, 1/4" X 2", 100/JAR	1 / JAR	6	☐

PRODUCT FEATURES

- Easy to Use Expansion Anchor
- Hammer Blow Forces the Nail to Expand for a Permanent, Reliable Fastening
- Drill the Anchor Hole Through the Material to be Fastened, Place Anchor into Hole and Drive the Pin
- Body: Zinc • Pin: Carbon Steel • Packaged in a Reusable Plastic Jar, 100 Anchors per Jar

TECHNICAL DATA

PART #	MODEL #	ANCHOR DIAMETER	ANCHOR LENGTH	DRILL BIT DIAMETER	MIN. EMBEDMENT	3000 PSI CONCRETE TENSION (LBS)	3000 PSI CONCRETE SHEAR (LBS)	WEIGHT PER JAR
H98364	HPFHD14X34J	1/4"	3/4"	1/4"	1/2"	261	884	2.0 LBS
H98365	HPFHD14X1J	1/4"	1"	1/4"	3/4"	261	884	2.5 LBS
H98366	HPFHD14X114J	1/4"	1-1/4"	1/4"	7/8"	261	884	2.5 LBS
H98367	HPFHD14X112J	1/4"	1-1/2"	1/4"	1"	261	884	2.5 LBS
H98368	HPFHD14X2J	1/4"	2"	1/4"	1"	261	884	3.4 LBS

Load values are manufacturer test data in 3000 PSI normal weight concrete.

JOB NAME:
JOB LOCATION:
CONTRACTOR:
DATE:
ITEM TAG:
ENGINEER APPROVAL:
DATE:
PART NUMBER:

www.hydrapro.biz | (877) 813-2333 | info@hydrapro.biz

Atlanta (GA) • Dallas (TX) • Houston (TX) • Pompano Beach (FL) • Jackson (MI) • Columbus (OH)