



STRIPE 3 SERIES MARKING PAINT

A fast drying marking paint designed to be sprayed in an inverted position. Produces vivid marks, does not clog, and is safe for grass. Meets APWA color standards and can be sprayed by hand or with the Z-605 marking gun or Z-606 marking wand.

Suggested Uses:

- Utility marking;
- Golf courses
- Landscaping
- Construction sites
- Surveying
- Mining



Packaging:

Cans per case	12
Shipping Weight	20 ounce cans: 20 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Hazard Class	2.1
Shipping Classification	limited quantity, UN 1950

Properties:

Coverage	Up to 500 linear feet
Cleanup	Paint or lacquer thinner
Flammability	Flammable
Flash point	-4F
Specific Gravity	0.73
Solids Content	16%
MIR value	0.48, cannot exceed 0.85
HAPs content	<1%
Storage Temperature	40-100F
Application Temperature	50-90F
Resin System	Lacquer
Shelf life	Guaranteed for 2 years
Freeze/Thaw	Up to 7 times without harm

****Do not warehouse in subfreezing temperatures**?**

Dry Time*:

To touch 1 hour

*At 72F, 50% humidity,
1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

AVAILABLE COLORS:

MODEL #	COLOR	MODEL #	COLOR
HPMPYEL	YELLOW 15 OZ.	HPMPORA	FLUORESCENT ORANGE 15 OZ.
HPMPRED	RED 15 OZ.	HPMPWHI	WHITE 15 OZ.
HPMPBLU	BLUE 15 OZ.	HPMPPNK	FLUORESCENT PINK 15 OZ.
HPMPGRE	GREEN 15 OZ.	HPMPBLA	BLACK 15 OZ.