


## TRANSITION FITTINGS MALE ADAPTERS CPVC x BRASS



No wrench here  
Use Teflon tape

Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	Select Model Below
<b>MALE ADAPTER CPVC x LEAD-FREE BRASS</b>					
H48200	<b>STD4704BTLF12</b>	1/2" CPVC X 1/2" MIP MALE ADAPTER	25	250	<input type="checkbox"/>
H48201	<b>STD4704BTLF34</b>	3/4" CPVC X 3/4" MIP MALE ADAPTER	25	250	<input type="checkbox"/>
H48202	<b>STD4704BTLF1</b>	1" CPVC X 1" MIP MALE ADAPTER	25	150	<input type="checkbox"/>
H48203	<b>STD4704BTLF114</b>	1 1/4" CPVC X 1 1/4" MIP MALE ADAPTER	10	80	<input type="checkbox"/>
H48204	<b>STD4704BTLF112</b>	1 1/2" CPVC X 1 1/2" MIP MALE ADAPTER	10	60	<input type="checkbox"/>
H48205	<b>STD4704BTLF2</b>	2" CPVC X 2" MIP MALE ADAPTER	5	20	<input type="checkbox"/>

- Lead Free
- Max working pressure 100 PSI @ 180° F
- Manufactured to ASTM Standard D2846



DIMENSIONS - Inch		
Size	A	B
1/2" MNPT x CPVC	0.99	1.81
3/4" MNPT x CPVC	1.24	2.09
1" MNPT x CPVC	1.50	2.60
1-1/4" MNPT x CPVC	1.88	3.07
1-1/2" MNPT x CPVC	2.15	3.31
2" MNPT x CPVC	2.65	3.90

### MATERIAL SPECIFICATION

PART	MATERIAL	SPECIFICATION
1 Solvent-weld socket tubing adapter	Virgin CPVC Resin	ASTM D1784 Class 23447
2 O-ring	EPDM Rubber	Commercial grade
3 Pipe thread adapter	Lead-Free Forged Brass	C46400

### Standards:

ANSI/ASME B1.20.1: Pipe threads, general purpose, Inch  
 ASTM D1784: Standard specification for rigid PVC and CPVC compounds  
 ASTM D2846: Standard specification for PVC and CPVC plastic hot-and cold-water distribution systems

**JOB NAME:**

**JOB LOCATION:**

**CONTRACTOR:**

**DATE:**

**ITEM TAG:**

**ENGINEER APPROVAL:**

**DATE:**

**PART NUMBER:**